

1/2-Inch  
DIGITAL METAL  
VIDEOCASSETTE

**XD** 1/2" DIGITAL  
**D-5**

# D5001

D5001



# The ultimate in high-quality D5 digital video performance.

## An Ideal Choice for Uncompressed Digital Recording

New Fujifilm D5001 videocassettes are designed to get the best out of today's 10-bit digital component recording systems. Thanks to newly developed ultra-fine, high-output metal magnetic particles and superior Fujifilm calendaring technology, the surface of the tape is mirror-smooth. So head contact is excellent, with minimal noise and low error rates. The result is a high C/N ratio, particularly in the short wavelength range that is essential for high-density digital recording.

## Superior Durability & Transport Stability

Fujifilm D5001 video tape uses a new high-adhesion binder material to assure outstanding reliability and minimal head clogging—even during extended still and high-speed shuttle operation. On long-playing 63M and 124L cassettes, durability is enhanced by an ultra-strong PEN (polyethylene naphthalate) base film that is exceptionally resistant to stretching and deformation. A new backcoating material contributes to stable tape transport by keeping the friction coefficient low under the most demanding operating conditions.


## Excellent Long-Term Storage Characteristics

Ultra-fine metal magnetic particles are coated with a powerful antioxidant to ensure that magnetic performance and output remain high even after long-term storage. In addition, our exclusive production technologies and high-quality base materials prevent the tape shrinkage that can cause tracking errors.

## High-Rigidity Precision Cassette Shells

High-rigidity cassette shells are precision-crafted to protect tape under adverse operating conditions. Tape transport remains stable because the tape is protected from deformation and damage, and the error rate remains low because dust and dirt cannot enter the shell. Cassettes are also equipped with two sliding plugs which can be used to individually protect the control and video signals against erasure.

Changes in Output Level after Still Playbacks (f=32 MHz)



### FUJIFILM D5001 Digital Videocassette Technical Data

Magnetic Properties	
Coercivity (Hc)	127.3 kA/m
Retentivity (Br)	265 mT
Physical Properties	
Thickness: Magnetic Layer	3.1 µm
: Total	13.5 µm
Tape Width	12.65 mm
Yield Strength	27 N
Breaking Tensile Strength	39 N
Residual Elongation	Less than 0.18%
Performance	
Video RF Output	0 dB*
Video C/N	0 dB*
Audio Sensitivity	0 dB*
Audio Frequency Response	0 dB*

Note: Figures are typical values of 33M tape based on FUJIFILM's standard measurement procedures.  
The Figures marked with \* are comparisons with the FUJIFILM reference tape.  
Specifications are subject to change without notice.

### FUJIFILM D5001 Digital Videocassette Line-up

Cassette	Size	Tape Length	Recording Time	Dimensions		Weight (Including Case)
				Cassette shell	Case	
S	23 S	223 <sup>+3</sup> m (732 ft.)	23 min.	161 x 98 x 25 mm	180 x 118 x 34 mm	325 g (0.72 lbs.)
	M	12 M	123 <sup>+3</sup> m (404 ft.)			
M	33 M	334 <sup>+3</sup> m (1096 ft.)	33 min.	212 x 124 x 25 mm	231 x 144 x 34 mm	477 g (1.05 lbs.)
	48 M	485 <sup>+3</sup> m (1591 ft.)	48 min.			
	63 M	635 <sup>+3</sup> m (2083 ft.)	63 min.			
L	94 L	947 <sup>+3</sup> m (3107 ft.)	94 min.	296 x 167 x 25 mm	315 x 187 x 34 mm	1,065 g (2.35 lbs.)
	124 L	1249 <sup>+3</sup> m (4098 ft.)	124 min.			



## FUJI PHOTO FILM CO., LTD.

26-30, NISHIAZABU 2-CHOME, MINATO-KU, TOKYO 106-8620, JAPAN

**Fuji Photo Film U.S.A., Inc.**  
Magnetic Markets Division 200 Summit Lake Drive, 2nd Floor Valhalla, New York 10595, U.S.A.  
**Fuji Photo Film Canada Inc.**  
600 Suffolk Court Mississauga, Ontario, L5R 4G4, Canada  
**Fuji Photo Film do Brasil Ltda.**  
Avenida Vereador Jose Diniz 3400, Campo Belo, Sao Paulo, CEP 04604-901, SP, Brasil  
**Fuji Magnetics G.m.b.H.**  
Fujistrasse 1, D-47533 Kleve, Germany  
**Fuji Photo Film (UK) Ltd.**  
Fuji Film House, 125 Finchley Road, Swiss Cottage, London NW3 6HY, U.K.  
**FUJIFILM Regional Services (Singapore) Pte Ltd.**  
10 New Industrial Road Singapore 536201